# **Material Safety Data Sheet**



Date of issue 28 September 2017 4.03

Version

#### 1. Product and company identification

Product name	: 830-130 EXPERT 0VOC PRIMER SEALER
Code	: 00382409
Manufacturer / Supplier	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)

2. Hazards identification			
Emergency overview	: WARNING!		
	MAY BE HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.		
	Avoid breathing vapor or mist. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.		
Potential acute health eff	ects		
Inhalation	: May be harmful if inhaled. Slightly irritating to the respiratory system.		
Ingestion	: May be harmful if swallowed.		
Skin	: No known significant effects or critical hazards.		
Eyes	: No known significant effects or critical hazards.		
Over-exposure signs/syn	nptoms		
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing		
Ingestion	: No specific data.		
Skin	: No specific data.		
Eyes	: No specific data.		
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.		

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS). (1988 Version)

See toxicological information (Section 11)

CAS number	% (w/w)
1317-65-3	10 - 30
13463-67-7	5 - 10
1332-58-7	5 - 10
•	1317-65-3 13463-67-7

#### Product name 830-130 EXPERT 0VOC PRIMER SEALER

### 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Notes to physician	<ul> <li>No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>

# 5. Fire-fighting measures

Flammability of the product	In a fire or if heated, a pressure increase will occur and the container may burst.	
Extinguishing media		
Suitable	Use an extinguishing agent suitable for the surrounding fire.	
Not suitable	None known.	
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suital training.	
Hazardous combustion products	Decomposition products may include the following materials: carbon oxides metal oxide/oxides	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained brea apparatus (SCBA) with a full face-piece operated in positive pressure mode.	athing

### 6. Accidental release measures

Personal precautions	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Product name 830-130 EXPERT 0VOC PRIMER SEALER

### 6. Accidental release measures

```
Small spill
```

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### 7. Handling and storage

Hand	ling
------	------

Storage

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not swallow. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 8. Exposure controls/personal protection

Name	Result	ACGIH	Ontario	Mexico	PPG
<b>∠</b> mestone	TWA	Not established	Not established	Not established	Not established
titanium dioxide	TWA	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> TD	10 mg/m <sup>3</sup>	Not established
Kaolin	TWA	2 mg/m <sup>3</sup> R	2 mg/m <sup>3</sup> R	2 mg/m <sup>3</sup> R	Not established

Key to abbrev	viations
---------------	----------

А	= Acceptable Maximum Peak	SR	<ul> <li>Respiratory sensitization</li> </ul>
ACGIH	<ul> <li>American Conference of Governmental Industrial Hygienists.</li> </ul>	SS	<ul> <li>Skin sensitization</li> </ul>
С	= Ceiling Limit	STEL	<ul> <li>Short term Exposure limit values</li> </ul>
F	= Fume	TD	= Total dust
IPEL	<ul> <li>Internal Permissible Exposure Limit</li> </ul>	TLV	<ul> <li>Threshold Limit Value</li> </ul>
R	= Respirable	TWA	<ul> <li>Time Weighted Average</li> </ul>
S	<ul> <li>Potential skin absorption</li> </ul>		

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures
 If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
 Engineering measures
 Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Product name 830-130 EXPERT 0VOC PRIMER SEALER

### 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Eyes	: Safety glasses with side shields.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Respiratory	: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# 9. Physical and chemical properties

Physical state	1	Liquid.
Flash point	1	Closed cup: Not applicable. [Product does not sustain combustion.]
Color	:	White.
Odor	:	Characteristic.
рН	1	9
<b>Boiling/condensation point</b>	1	100°C (212°F)
Melting/freezing point	1	Not available.
Specific gravity	1	1.33
Density(lbs / gal)	1	11.1
Vapor pressure	1	3.3 kPa (25 mm Hg) [room temperature]
Vapor density	1	Not available.
Volatility	1	69% (v/v), 51.659% (w/w)
Evaporation rate	1	0.05 (butyl acetate = 1)
Solubility	1	Partially soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	:	Not available.
% Solid. (w/w)	1	48.341

#### Product name 830-130 EXPERT 0VOC PRIMER SEALER

### 10. Stability and reactivity

Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
	alkalis
Materials to avoid	: Reactive or incompatible with the following materials:,acids,oxidizing materials,strong
Conditions to avoid	: No specific data.
Stability	: Stable under recommended storage and handling conditions (see Section 7).

### 11. Toxicological information

Product/ingredient name		Result	Species	Dose	Exposure
titanium dioxide Kaolin		LD50 Oral LD50 Oral	Rat Rat	>11 g/kg >5000 mg/kg	
Conclusion/Summary Chronic toxicity	: Not av	ailable.	·		
Conclusion/Summary	: Not av	ailable.			
<u>Target organs</u>	Contai		ay cause damage t	e following organs: e o the following organ	
<u>Carcinogenicity</u>					
Carcinogenicity Classification		ins material which ma ds on duration and le	•	ased on animal data.	Risk of cancer
		ACGIH	IARC	NT	P
Product/ingredient name		A4	2B		

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be

a human carcinogen

Not listed or regulated as a carcinogen: -

# 12. Ecological information

**Environmental effects** 

: No known significant effects or critical hazards.

#### Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

# 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a

Canada - Mexico Page: 5/7

#### Product name 830-130 EXPERT 0VOC PRIMER SEALER

### 13. Disposal considerations

safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### 14. Transport information

	TDG	Mexico	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

TDG : None identified. : None identified. **Mexico** IMDG

: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory information			
Canada inventory ( DSL )	: At least one component is not listed.		
<u>Canada</u> WHMIS (Canada) <u>Mexico</u> Classification	: Class D-2A: Material causing other toxic effects (Very toxic).		
	lealth : 1 Reactivity : 0		

Product name 830-130 EXPERT 0VOC PRIMER SEALER

### 16. Other information

Hazardous Material Information System (U.S.A.) Health : 1 \* Flammability : 0 Physical hazards : 0 (\*) - Chronic effects Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal haza

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 1 Flammability : 0 Instability : 0

Date of previous issue: 8/23/2017Organization that prepared: EHS

the MSDS

✓ Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.